



MASKING

NARCAR

Self-adhesive tape with lightly crepe paper backing and adhesive with natural rubber and resins base in solvent.

Thanks to its excellent adhesive quality, this tape is used mostly in the carbody sector and industrial painting jobs.

TECHNICAL SPECIFICATIONS

BACKING

Lightly crepe paper

ADHESIVE

Natural rubber, hydrocarbonic and natural resins, pigments, plasticizers and antioxidants

	NARCAR	NARCAR S	
Backing weight	60 g/sqm	76 g/sqm	± 10 %
Total thickness	135 µ	150 µ	± 10 %
Adhesion	2,9 N/cm	2,9 N/cm	± 10 %
Stretch at breaking point	10 %	10 %	± 20 %
Breaking load	35 N/cm	38 N/cm	± 10 %
Heat resistance for 90 min.	80° C	80° C	
Heat resistance for 30 min.	110° C	110° C	
Colours	YELLOW WHITE BROWN	YELLOW WHITE	

THE ABOVE VALUES ARE THE AVERAGE RESULTS OF TESTS MADE ON OUR STANDARD PRODUCTION AND ARE THEREFORE NOT LEGALLY BINDING.

COMPANY WITH QUALITY MANAGEMENT
SYSTEM CERTIFIED BY DNV
= ISO 9001:2008 =

NAR S.p.A. Via Leonardo da Vinci, 8 Z.I. - 35020 LEGNARO (PD) Italy
Telephone ++39 049 883 02 33 - Telefax ITA ++39 049 883 02 44 - Telefax EXP ++39 049 883 02 55
E-mail: narspa@nar-spa.com - www.nar-spa.com



STANDARD SIZES

ROLLS PER BOX

LENGTH IN METRES		WIDTH IN MM.		
50	x	12		72 / 150
50	x	15		60 / 120
50	x	19		48 / 96
50	x	25		36 / 72
50	x	30		30 / 60
50	x	38		24 / 48
50	x	50		18 / 36
50	x	75		12 / 24

OTHER SIZES AND PACKS ARE AVAILABLE ON REQUEST. PLEASE CONTACT OUR CUSTOMER SERVICE.



RECOMMENDATIONS FOR THE USE

- IT IS GOOD PRACTICE TO USE THE PRODUCT WITHIN 6 MONTHS FROM PURCHASE DATE. THE UNROLLING STRENGTH OF THE TAPE NORMALLY INCREASES IN TIME.
- THE TAPE MUST BE KEPT IN A DRY PLACE, PREFERABLY AT A TEMPERATURE BETWEEN 15°C AND 25°C. IF THE STORAGE TEMPERATURE IS DIFFERENT, BRING THE TAPE BACK TO ABOVE LEVEL BEFORE USING IT. KEEP IT OUT OF THE LIGHT.
- THE ROLLS MUST BE STORED HORIZONTALLY AND KEPT IN THEIR ORIGINAL PACKING.
- HANDLE THE PRODUCT WITH CARE TO AVOID DAMAGING IT AND CONSEQUENTLY, ALTERING ITS CORRECT USE.
- REMOVE THE TAPE SLOWLY WITHOUT TEARING IT UP, AT AN IDEAL TEMPERATURE OF 20°C TO 30°C, NOT TO HAVE RESIDUES LEFT OR BREAKING.
- THE VALUES INDICATED IN THIS DATA SHEET REFER TO RESULTS OF TESTS MADE ON THE PRODUCT JUST MANUFACTURED. THE AESTHETIC AND TECHNICAL FEATURES OF THE TAPE MAY BE SUBJECT TO SOME CHANGES CONSEQUENT ON AGEING, EVEN THOUGH THE QUALITY LEVEL OF THE PRODUCT IS MAINTAINED.
- THIS PRODUCT HAS A WIDE RANGE OF APPLICATIONS. HOWEVER IT IS ADVISABLE TO CHECK THE USE IT IS MEANT FOR, THE SURFACE OF APPLICATION, ITS CLEANLINESS AND THE TEMPERATURE TO WITHSTAND.

NAR IS AT YOUR DISPOSAL FOR ANY FURTHER INFORMATION.

Under normal conditions the tape is not toxic and does not generally cause problems on contact with the skin. However, normal precautions should be taken in handling it and hands should be washed after use. The tape is not approved for medical use, for bandaging and contact with foodstuff.