



MASKING

NARPAPER

Self-adhesive tape with lightly crepe paper backing and synthetic rubber base adhesive. Practical, economic, it sticks to every surface and is used for general purpose applications.

TECHNICAL SPECIFICATIONS

BACKING

Lightly crepe paper

ADHESIVE

Synthetic rubber, hydrocarbonic and natural resins, pigments, plasticizers and antioxidants

Backing weight	55 g/sqm	± 10 %
Total thickness	130 µ	± 10 %
Adhesion	4,0 N/cm	± 10 %
Stretch at breaking point	10 %	± 20 %
Breaking load	35 N/cm	± 10 %
Colours	WHITE YELLOW	

THE ABOVE VALUES ARE THE AVERAGE RESULTS OF TESTS MADE ON OUR STANDARD PRODUCTION AND ARE THEREFORE NOT LEGALLY BINDING.



STANDARD SIZES

ROLLS PER BOX

LENGTH IN METRES		WIDTH IN MM.		
50	x	15		60 / 120
50	x	19		48 / 96
50	x	25		36 / 72
50	x	30		30 / 60
50	x	38		24 / 48
50	x	50		18 / 36
50	x	75		12 / 24

OTHER SIZES AND PACKS ARE AVAILABLE ON REQUEST. PLEASE CONTACT OUR CUSTOMER SERVICE.



RECOMMENDATIONS FOR THE USE

- IT IS GOOD PRACTICE TO USE THE PRODUCT WITHIN 6 MONTHS FROM PURCHASE DATE. THE UNROLLING STRENGTH OF THE TAPE NORMALLY INCREASES IN TIME.
- THE TAPE MUST BE KEPT IN A DRY PLACE, PREFERABLY AT A TEMPERATURE BETWEEN 15°C AND 25°C. IF THE STORAGE TEMPERATURE IS DIFFERENT, BRING THE TAPE BACK TO ABOVE LEVEL BEFORE USING IT. KEEP IT OUT OF THE LIGHT.
- THE ROLLS MUST BE STORED HORIZONTALLY AND KEPT IN THEIR ORIGINAL PACKING.
- HANDLE THE PRODUCT WITH CARE TO AVOID DAMAGING IT AND CONSEQUENTLY, ALTERING ITS CORRECT USE.
- THE VALUES INDICATED IN THIS DATA SHEET REFER TO RESULTS OF TESTS MADE ON THE PRODUCT JUST MANUFACTURED. THE AESTHETIC AND TECHNICAL FEATURES OF THE TAPE MAY BE SUBJECT TO SOME CHANGES CONSEQUENT ON AGEING, EVEN THOUGH THE QUALITY LEVEL OF THE PRODUCT IS MAINTAINED.
- THIS PRODUCT HAS A WIDE RANGE OF APPLICATIONS. HOWEVER IT IS ADVISABLE TO CHECK THE USE IT IS MEANT FOR, THE SURFACE OF APPLICATION, ITS CLEANLINESS AND THE TEMPERATURE TO WITHSTAND.

NAR IS AT YOUR DISPOSAL FOR ANY FURTHER INFORMATION.