



PACKAGING TAPES

ACRILNAR SM high tack

Self-adhesive tape in Polypropylene with acrylic water base highly adhesive mass and noiseless unrolling.

Available also in sizes printable with corona treatment (SM XHT), which makes the tape unwind silently.

This tape has high resistance to ageing caused by light sources and excellent performance during applications at high and low room temperatures. It is free from organic solvent.

TECHNICAL SPECIFICATIONS

BACKING

Polypropylene film

ADHESIVE

Acrylic water base pigments

ACRILNAR SM XHT ACRILNAR SM N.N. XHT

Backing thickness	35 μ	$\pm 10 \%$
Total thickness	63 μ	$\pm 10 \%$
Adhesion	3,8 N/cm	$\pm 10 \%$
Stretch at breaking point	145 %	$\pm 20 \%$
Breaking load	52 N/cm	$\pm 10 \%$
Colours	BROWN WHITE TRANSPARENT	

THE ABOVE VALUES ARE THE AVERAGE RESULTS OF TESTS MADE ON OUR STANDARD PRODUCTION AND ARE THEREFORE NOT LEGALLY BINDING.

COMPANY WITH QUALITY MANAGEMENT
SYSTEM CERTIFIED BY DNV
= ISO 9001:2008 =

NAR S.p.A. Via Leonardo da Vinci, 8 Z.I. - 35020 LEGNARO (PD) Italy
Telephone ++39 049 883 02 33 - Telefax ITA ++39 049 883 02 44 - Telefax EXP ++39 049 883 02 55
E-mail: narspa@nar-spa.com - www.nar-spa.com



ACRILNAR SM NN XHT

STANDARD SIZES

ROLLS PER BOX

66	x	38	48
66	x	48	36
66	x	50	36
ACRILNAR SM XHT			
990	x	150	2

OTHER SIZES AND PACKS ARE AVAILABLE ON REQUEST. PLEASE CONTACT OUR CUSTOMER SERVICE.

! RECOMMENDATIONS FOR THE USE

- IT IS GOOD PRACTICE TO USE THE PRODUCT WITHIN 6 MONTHS FROM PURCHASE DATE. THE UNROLLING STRENGTH OF THE TAPE NORMALLY INCREASES IN TIME.
- THE TAPE MUST BE KEPT IN A DRY PLACE, PREFERABLY AT A TEMPERATURE BETWEEN 15°C AND 25°C. IF THE STORAGE TEMPERATURE IS DIFFERENT, BRING THE TAPE BACK TO ABOVE LEVEL BEFORE USING IT.
- UNROLLING THE TAPE IS NOISIER AT LOW TEMPERATURES. THE TAPE UNWIND IMPROVES ITS NOISELESS CHARACTERISTIC WITH AGEING.
- THE ROLLS MUST BE STORED HORIZONTALLY AND KEPT IN THEIR ORIGINAL PACKING.
- HANDLE THE PRODUCT WITH CARE TO AVOID DAMAGING IT AND CONSEQUENTLY, ALTERING ITS CORRECT USE.
- THE VALUES INDICATED IN THIS DATA SHEET REFER TO RESULTS OF TESTS MADE ON THE PRODUCT JUST MANUFACTURED. THE AESTHETIC AND TECHNICAL FEATURES OF THE TAPE MAY BE SUBJECT TO SOME CHANGES CONSEQUENT ON AGEING, EVEN THOUGH THE QUALITY LEVEL OF THE PRODUCT IS MAINTAINED.
- THIS PRODUCT HAS A WIDE RANGE OF APPLICATIONS. HOWEVER IT IS ADVISABLE TO CHECK THE USE IT IS MEANT FOR, THE SURFACE OF APPLICATION AND ITS CLEANLINESS.

NAR IS AT YOUR DISPOSAL FOR ANY FURTHER INFORMATION.

Under normal conditions the tape is not toxic and does not generally cause problems on contact with the skin. However, normal precautions should be taken in handling it and hands should be washed after use. The tape is not approved for medical use, for bandaging and contact with foodstuff.